



Product of India

SOLID RESILIENT TYRES



SOLO	E2
Grade	ECONOMY
Design	2-stage, Special low heat build up natural rubber tread
Ride	Firm
Operating Conditions	Up to 10 hrs for light duty and intermittent use
Advantages	Value priced, stable design

TYRE SPECIFICATIONS

TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tyre dimensions in mm			Load capacity on fork lifts, kg at 25kmph	
				Outer Dia.	Sidewall width	Tread width	Load wheel	Steer wheel
3.00 - 4		2.10	RIB	245	85	75	260	195
3.50 - 4		2.10	RIB	250	89	83	260	195
4.00 - 4		2.50	LUG	300	92	84	535	412
3.50 - 5		3.00	RIB	300	100	90	900	690
4.00 - 8		2.75, 3.00	LUG, RIB	402	103	86	950	730
4.00 - 8		3.75	RIB	405	119	86	950	730
12x3 1/2 - 8		3.00	SM	308	98	87	850	650
	100/80-8	2.50	SM	360	105	90	1,000	770
15X4 1/2 - 8	125/75-8	3.00	LUG	368	105	90	1,040	800
15X4 1/2 - 8	125/75-8	3.00	SM	378	110	100	1,040	800
5.00 - 8		3.00	LUG	450	120	110	1,415	1,090
5.00 - 8		3.75	RIB	450	125	110	1,415	1,090
16X6 - 8	150/75-8	4.33	LUG	406	140	125	1,270	975
17X7 - 8		4.33	SM	430	150	134	2,000	1,540
18X7 - 8	180/70-8	4.33	LUG	450	157	142	2,145	1,650
	140/55 - 9	4.00	LUG	376	125	110	1,170	900
6.00 - 9		4.00	LUG	520	138	120	1,885	1,450
21X8 - 9	200/75-9	6.00	LUG	517	188	157	2,755	2,120
	200/50 - 10	6.50	LUG	454	190	160	2,470	1,900
6.50 - 10		5.00, 5.50	LUG	566	160	140	2,340	1,800
7.50 - 10		5.00, 5.50	LUG	630	170	150	3,070	2,360
23X9 - 10	225/75-10	6.50	LUG	580	194	178	3,160	2,430
7.00 - 12		5.00	LUG	646	172	150	2,920	2,240
23X10 - 12		8.00	LUG	580	232	200	3,770	2,900
27X10 - 12	250/75-12	8.00	LUG	672	240	200	3,900	3,000
23X5 - 13		3.75	LUG	605	122	102	1,495	1,150
7.00 - 15		5.50	LUG	705	180	158	3,545	2,725
7.50 - 15		5.50, 6.00, 6.50	LUG	736	193	168	3,900	3,000
8.15 - 15 (28X9-15)	225/75-15	7.00	LUG	678	221	190	3,445	2,650
8.25 - 15		6.50	LUG	808	192	173	4,750	3,650
2.50 - 15	250/70-15	7.00, 7.50	LUG	706	220	190	4,745	3,650
3.00 - 15	315/70-15	8.00	LUG	806	242	223	5,850	4,500
28X12.5-15	345/45-15	9.75	LUG	705	275	255	5,525	4,250
	355/65-15	9.75	LUG	810	285	265	7,000	5,450
	400/60-15	11.00	LUG	810	318	298	8,970	6,900
7.50 - 16		5.50, 6.00, 6.50	LUG	736	193	168	3,900	3,000
8.25 - 16		5.50, 6.00	LUG	808	192	173	4,750	3,650
7.50 - 20		6.00	LUG	870	200	175	3,900	3,250
8.25 - 20		6.50	LUG	915	200	180	4,380	3,650
	355/50 - 20	10.00	SM	810	285	265	8,970	6,900
9.00 - 20		6.50, 7.00	LUG	972	226	191	5,400	4,500
10.00 - 20		7.50, 8.00, 8.50	LUG	1,004	250	203	6,000	5,000
10.00 - 20		7.50, 8.00, 8.50	SM	1,050	265	235	6,000	5,000
11.00 - 20		7.50, 8.00, 8.50	SM	1,050	265	235	6,000	5,000
12.00 - 20		8.00, 8.50	LUG	1,080	255	232	7,560	6,300
12.00 - 20		8.00, 8.50	SM	1,140	295	250	7,560	6,300
13.00 - 20		8.00, 8.50	SM	1,140	295	250	7,560	6,300
12.00 - 24		8.50, 10.00	LUG	1,165	265	230	8,040	6,700
14.00 - 24		10.00	LUG	1,275	308	270	11,100	9,250
14.00 - 25		10.00	LUG	1,275	308	270	11,100	9,250

All dimensions are nominal and we reserve the right to make changes any time without notice

Available in Black and Non Marking treads, with or without Clip.

Website: www.sun-tws.com

Contact: crm@sun-tws, info@sun-tws.com

Corporate Office:

SUN TYRE & WHEEL SYSTEMS

180 Mount Road, Chennai 600006, India

Phone #: +91-44-28525289

Manufacturing locations:

Plant #1 at A1-F3/A, New Sidco Industrial Estate

Maraimalainagar 603209, India

Plant #2 at Lot 2, Block B, Biyagama Export Processing Zone

Colombo, Sri Lanka

Plant # 3 *Under Construction* @

7/B1, Sipcot Industrial Complex, Pudukottai,

Tamil Nadu, India