



TALON

SUN-TWS
SUN TIRE & WHEEL SYSTEMS

This page includes
Industrial Pneumatic Tires | SKID STEER

SKID STEER

SEGMENT	SUB SEGMENT	TIRE SIZE	PATTERN	PR	LOAD INDEX	TYPE	REMARKS IF ANY	RIM WIDTH	ALT. RIM	UNLOADED INFLATED DIMENSIONS±2%		NSD		LOAD CAPACITY (KG)			LOAD CAPACITY SPEED	IP BAR
										OD (MM)	SW (MM)	32 nd of inch	mm	Side Loaders Static Okmh	LOAD WHEEL	STEER WHEEL		
Industrial	Skid Steer	10-16.5	ST30	6		TL		8.25		775	280				1590 1255		8 KMH 16 KMH	3.10
Industrial	Skid Steer	10-16.5	ST30	8		TL		8.25		775	280				1880 1485		8 KMH 16 KMH	4.10
Industrial	Skid Steer	10-16.5	ST30	8		TL	(BA)	8.25		775	280				2135 1685		8 KMH 16 KMH	5.20
Industrial	Skid Steer	10-16.5	ST45	8		TL	(HIWALL)	8.25		770	280				1590 1255		8 KMH 16 KMH	3.10
Industrial	Skid Steer	10-16.5	ST30	10		TL		8.25		775	280				2135 1685		8 KMH 16 KMH	5.10
Industrial	Skid Steer	10-16.5	ST45	10		TL	(HIWALL)	8.25		770	280				1880 1485		8 KMH 16 KMH	4.10
Industrial	Skid Steer	10-16.5	IT30	10		TL		8.25		790	280				2135 1685		8 KMH 16 KMH	5.10
Industrial	Skid Steer	12-16.5	ST30	8		TL		9.75		845	330				2180 1720		8 KMH 16 KMH	3.40
Industrial	Skid Steer	12-16.5	ST30	10		TL		9.75		845	330				2540 2010		8 KMH 16 KMH	4.50
Industrial	Skid Steer	12-16.5	ST45	10		TL	(HIWALL)	9.75		840	315				2890 2285		8 KMH 16 KMH	5.60
Industrial	Skid Steer	12-16.5	ST30F	10		TL		9.75		845	325				2540 2010		8 KMH 16 KMH	4.50
Industrial	Skid Steer	12-16.5	ST30F	12		TL		9.75		845	325				2890 2285		8 KMH 16 KMH	5.60
Industrial	Skid Steer	12-16.5	ST30	12		TL		9.75		845	330				2890 2285		8 KMH 16 KMH	5.60
Industrial	Skid Steer	12-16.5	ST30	12		TL	(BA)	9.75							2540 2005		8 KMH 16 KMH	4.50
Industrial	Skid Steer	12-16.5	ST45	12		TL	(HIWALL)	9.75		840	315				2540 2010		8 KMH 16 KMH	4.50
Industrial	Skid Steer	12-16.5	IT30	12		TL		9.75		835	330				2865 2265		8 KMH 16 KMH	5.50
Industrial	Skid Steer	12-16.5	IT30	14		TL		9.75		835	330				3065 2420		8 KMH 16 KMH	6.20
Industrial	Skid Steer	12-16.5	ST30F	8		TL		9.75		845	325				2180 1720		8 KMH 16 KMH	3.40
Industrial	Skid Steer	14-17.5	ST30	14		TL		10.50		945	360				3875 3060		8 KMH 16 KMH	5.50
Industrial	Skid Steer	15-19.5	ST30	14		TL		11.75		1020	415				4565 3605		8 KMH 16 KMH	4.85
Industrial	Skid Steer	23X8.50-12	ST30	6		TL		7.00		575	125				820 650		8 KMH 16 KMH	3.40

SEGMENT	SUB SEGMENT	TIRE SIZE	PATTERN	PR	LOAD INDEX	TYPE	REMARKS IF ANY	RIM WIDTH	ALT. RIM	UNLOADED INFLATED DIMENSIONS±2%		NSD		LOAD CAPACITY (KG)			LOAD CAPACITY SPEED	IP BAR
										OD (MM)	SW (MM)	32 nd of inch	mm	Side Loaders Static Okmh	LOAD WHEEL	STEER WHEEL		
Industrial	Skid Steer	23X8.50-12	ST30	8		TL		7.00		575	215				955 755		8 KMH 16 KMH	4.40
Industrial	Skid Steer	23X8.50-12	ST30	12		TL		7.00		575	215				1080 855		8 KMH 16 KMH	5.40
Industrial	Skid Steer	27X10.5-15	ST30	8		TL		8.50		700	260				1280 1010		8 KMH 16 KMH	3.50
Industrial	Skid Steer	27X10.5-15	ST30	12		TL		8.50		700	260				1560 1235		8 KMH 16 KMH	4.90
Industrial	Skid Steer	27X10.5-15	ST30	6		TL		7.00		680	210				1030 815		8 KMH 16 KMH	3.40
Industrial	Skid Steer	27X10.5-15	ST30	8		TL		7.00		680	210				1250 990		8 KMH 16 KMH	4.80
Industrial	Skid Steer	31X15.5-15	ST30	10		TL		13.00		810	390				2500 1960		8 KMH 16 KMH	4.20
Industrial	Skid Steer	31.5X13-16.5	ST30	10		TL		9.75		795	325				2435 1925		8 KMH 16 KMH	4.80
Industrial	Skid Steer	33X15.5-16.5	ST30	12		TL		12.00		860	390				3145 2485		8 KMH 16 KMH	4.80

IT 30



ST 30



ST 45

